

Inverter (Special for Australia)

ZDNY1500B-2800B



Inverter Model	ZDNY1500B	ZDNY2200B	ZDNY2800B
Input (DC)			
Max. recommended DC power [W]	1700	2300	3000
Max. DC voltage [V]	550	550	550
Total max. input current [A]	9	11	13.5
MPPT voltage range [V]	180~500	200~500	210~500
Min. DC Voltage / start voltage [V]	70 / 100	70 / 100	70 / 100
Number of MPP trackers / strings per MPP tracker	1 / 1	1 / 1	1 / 1
Output (AC)			
AC nominal power [W]	1500	2000	2600
Max. AC power [W]	1650	2200	2800
Nominal AC voltage; range [V]	230/180~270*	230/180~270*	230/180~270*
Max. AC current [A]	8.6	11	13.8
AC grid frequency; range [Hz]	50 / 47~52*	50 / 47~52*	50 / 47~52*
Power factor	1	1	1
Total harmonic distortion (THD)	<3% (nominal power)	<3% (nominal power)	<3% (nominal power)
Efficiency			
MPPT efficiency	99.9%	99.9%	99.9%
Euro-efficiency	95.8%	96.2%	96.3%
Max. efficiency	96.8%	96.8%	97.0%
General data			
Degree of protection	IP65	IP65	IP65
Cooling concept	Convection	Convection	Convection
Topology	transformerless	transformerless	transformerless
Internal consumption (night) [W]	0	0	0
Noise emission (typical) [dB]	<30	<30	<30
Communication interfaces	RS485 / RS232	RS485 / RS232	RS485 / RS232
LCD display	Backlight, 16*2 Character LCD	Backlight, 16*2 Character LCD	Backlight, 16*2 Character LCD
Dimensions (W / H / D) [mm]	332 / 450 / 161	332 / 450 / 161	332 / 450 / 161
Weight [kg]	17.1	17.5	17.9
Operating temperature range [°C]	-20~+60 (derating at 45)	-20~+60 (derating at 45)	-20~+60 (derating at 45)
Standard warranty [year]	5	5	5
Inverter Model	ZDNY1500B	ZDNY2200B	ZDNY2800B